

XTX-PA SERIES Thermoformers



PlastiVac's plug-assist **PA** configuration can be added to our XTX model for applications requiring draw depths up to 38". PVI's PA thermoforming machines are ideal for heavy-duty applications requiring positive and negative molds, high definition and deep draws. Standard twin heater enables use of plastic sheets up to 3/4" thick. Fully automatic with freestanding PLC and remote control consoles. PA and DE configurations can be combined for higher output.

XTX-PA machines are available in the following stock sizes:

Model	Platen Size	Clamping Frame Size	Standard Draw Depth
404XTX-PA	4' x 4'	52" x 52"	22"
406XTX-PA	4' x 6'	52" x 76"	22"
408XTX-PA	4' x 8'	52" x 100"	22"
4100XTX-PA	4' x 10'	52" x 124"	26"
4120XTX-PA	4' x 12'	52" x 148"	26"
608XTX-PA	6' x 8'	76" x 100"	30"
6100XTX-PA	6' x 10'	76" x 124"	30"
6120XTX-PA	6' x 12'	76" x 148"	30"
6140XTX-PA	6' x 14'	76" x 172"	30"
6160XTX-PA	6' x 16'	76" x 196"	30"
6180XTX-PA	6' x 18'	76" x 220"	30"
8100XTX-PA	8' x 10'	100" x 124"	36"
8120XTX-PA	8' x 12'	100" x 148"	36"
8140XTX-PA	8' x 14'	100" x 172"	36"
8160XTX-PA	8' x 16'	100" x 196"	36"
8200XTX-PA	8' x 20'	100" x 244"	38"

Custom sizes up to 10' x 24'